

(19)



Eur päisches Patentamt
European Patent Office
Offic européen des br vets



(11) Publication number:

0 556 662 A1

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 93101779.2

(22) Date of filing: 05.02.93

(51) Int. Cl.⁵: **C10M 111/04**, **C10M 169/04**,
C10M 171/00, //(C10M111/04,
105:06,105:36,105:38,105:42,
107:10),(C10M169/04,105:06,
107:10,129:72,129:74,129:78),
C10N40:30

(30) Priority: 18.02.92 JP 30529/92

(43) Date of publication of application:
25.08.93 Bulletin 93/34

(94) Designated Contracting States:
BE CH DE FR GB IT LI NL SE

(71) Applicant: **IDEMITSU KOSAN COMPANY
LIMITED**
1-1, 3-chome, Marunouchi Chiyoda-ku
Tokyo(JP)

(72) Inventor: **Katafuchi, Tadashi**, c/o Idemitsu
Kosan Co., Ltd.
24-4, Anesakikaigan
Ichihara-shi, Chiba-ken(JP)
Inventor: **Nakamura, Akira**, c/o Idemitsu
Kosan Co., Ltd.
24-4, Anesakikaigan
Ichihara-shi, Chiba-ken(JP)

(74) Representative: **Türk, Gille, Hrabal, Leifert**
Brucknerstrasse 20
D-40593 Düsseldorf (DE)

(54) Lubricant for refrigerating machine employing refrigerant comprising tetrafluoroethane.

(57) There has been disclosed herein a lubricant for refrigerating machines employing as a refrigerant 1,1,1,2-tetrafluoroethane or 1,1,2,2-tetrafluoroethane which comprises as an essential component a base oil comprising (A) 40 to 95% by weight of a synthetic oil formed of a poly- α -olefin or a mixture of a poly- α -olefin and an alkylbenzene and (B) 5 to 60% by weight of a fluidity improver formed of both or either of an ester compound and a triglyceride. The lubricant is used along with a substitute flon refrigerant, and is excellent in the performance such as wear resistance, electrical insulating properties, hydrolytic stability, nonhygroscopicity, etc. and also in returnability of the lubricant. Thus, the lubricant is especially effective when used in automobile or household air conditioner, refrigerator, etc. having high industrial usefulness.

EP 0 556 662 A1

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a lubricant for refrigerating machines employing a refrigerant comprising tetrafluoroethane. More particularly, it relates to a lubricant for refrigerating machines which is used along with substitute fluorohydrocarbon (hereinafter sometimes referred to as "flon compound") such as 1,1,1,2-tetrafluoroethane (R-134a). As such, the lubricant is excellent in the performance such as wear resistance, electrical insulating properties, hydrolytic stability, nonhygroscopicity and the like and further has
 10 excellent returnability of the lubricant in a refrigerating cycle (characteristics that the lubricant is inclined to return to a compressor after it is circulated in the refrigerating cycle).

2. Description of the Related Arts

15 Conventionally, in a compression-type refrigerating cycle comprising a compressor, a condenser, an expansion valve and an evaporator, a flon compound including a fluorinated hydrocarbon such as dichlorodifluoromethane (R-12) and chlorodifluoromethane (R-22) has been used as the refrigerant. Many kinds of lubricants compatible with them have been produced industrially available for use.

However, there have been misgivings that these flon compounds widely used as the refrigerant are
 20 liable to cause depletion of the ozone layer and environmental pollution after they are released into the open air. In an effort to prevent environmental pollution, fluorohydrocarbons (or chlorofluorohydrocarbons), for example 1,1,1,2-tetrafluoroethane (R-134a) and the like have been developed as a possible replacement in recent years. Until now there have been introduced into market many so-called substitute flon compounds with minimized danger of environmental pollution and capable of satisfying said required
 25 properties, for example 1,1,2,2-tetrafluoroethane (R-134) and the like, as well as R-134a.

These new substitute flon refrigerants are different from conventional flon refrigerants in characteristics. Thus, glycol compounds, ester compounds and the like have been proposed as the lubricant for use in combination with them (US Patent No. 4,755,316, Japanese Patent Applications Laid Open No. 33193/1991, No. 200895/1991, No. 200896/1991, No. 20975/1992 and No. 4294/1992), and these patents
 30 are intended to dissolve substitute flon refrigerants and lubricants completely so as to provide good returnability of the lubricants.

In an attempt to circulate all over a refrigerating cycle a refrigerant and a lubricant in their completely dissolved state as envisaged by these patents, however, said lubricant must be selected from only a very limited number of compounds acceptable to the chemical properties of substitute flon refrigerants such as
 35 R-134a. Accordingly, the selected lubricant is forced to sacrifice certain aspects of the important performance required as the lubricant.

In fact, polyalkylene glycol compounds and ester compounds thereof, both known as compatible with R-134a, have been found to have insufficient wear resistance, along with faulty electrical insulating properties. It has also been found that the polyalkylene glycol compounds are highly hygroscopic while the ester
 40 compounds thereof are unstable hydrolytically. Thus the demand for a solution in these problems has been raised in relevant industrial segments.

The present invention has been completed on the basis of a concept quite contrary to ordinary common knowledge as set forth above, in an effort to find the solution in the problems. As the result, it has been found that all these aspects of the performance can be unified by using a substance excellent in wear
 45 resistance, insulation resistance and the like as the lubricant, compounding therewith a fluidity improver to improve the fluidity of the lubricant in the presence of a refrigerant (R134a and the like) and thus providing excellent returnability of the lubricant in a compression-type refrigerating cycle. It has thus been made possible that a lubricant combined even with a new refrigerant has all the required performance including excellent wear resistance, electrical insulating properties, hydrolytic stability and the like and further
 50 ensuring excellent returnability of the lubricant. The present invention has been accomplished based on this finding.

SUMMARY OF THE INVENTION

55 Therefore, an object of the present invention is to provide a lubricant for refrigerating machines employing a refrigerant comprising tetrafluoroethane, which is excellent in the performance such as wear resistance, electrical insulating properties, hydrolytic stability, nonhygroscopicity and especially has excellent returnability of the lubricant. The lubricant can be used in combination with a substitute flon

refrigerant in a compression-type refrigerating cycle without a hitch.

Another object of the present invention is to provide a lubricant for refrigerating machines employing a refrigerant comprising tetrafluoroethane, which is especially effective when used in automobile or household air conditioners, refrigerators and the like, having high industrial usefulness.

5 The present invention provides a lubricant for refrigerating machines employing a refrigerant comprising 1,1,1,2-tetrafluoroethane or 1,1,2,2-tetrafluoroethane which comprises as an essential component a base oil comprising (A) 40 to 95% by weight of a synthetic oil formed of a poly- α -olefin or a mixture of a poly- α -olefin and an alkylbenzene and (B) 5 to 60% by weight of a fluidity improver comprising both or either of an ester compound and a triglyceride.

10 The lubricant of the present invention can be suitably used in various refrigerating machines and ordinarily in a compression-type refrigerating cycle comprising a compressor, a condenser, an expansion valve and an evaporator.

DESCRIPTION OF PREFERRED EMBODIMENTS

15 As set forth above, the lubricant of the present invention comprises the components (A) and (B) as the essential components, and the synthetic oil constituting the component (A) is a poly- α -olefin or a mixture of a poly- α -olefin and an alkylbenzene.

Various poly- α -olefins can be used and ordinarily are each a polymer of α -olefin having 8 to 14 carbon atoms and a kinematic viscosity of 10 to 350cSt at 40°C. Preferred among them is a polymer of 1-dodecene, a polymer of 1-decene or a polymer of 1-octene, each having a kinematic viscosity of 10 to 350cSt at 40°C. A lubricant containing a synthetic oil comprising such a poly- α -olefin has a lower viscosity at low temperatures to provide better returnability of the lubricant.

Various alkylbenzenes can be used as well and ordinarily are each an alkylbenzene having a kinematic viscosity of 5 to 500cSt, preferably 10 to 350cSt at 40°C. Either soft or hard alkylbenzene can be used provided that it meets the above-mentioned condition.

The alkylbenzene is not used singly but in the form of its mixture with said poly- α -olefin as the synthetic oil as the component (A) of the present invention. The mixing ratio of the poly- α -olefin and the alkylbenzene is appropriately selected according to circumstances and is not particularly limited. Preferably 30 the mixture has a poly- α -olefin content of 5% or more by weight, more preferably 50% or more by weight of the mixture. When the mixture of the poly- α -olefin and the alkylbenzene is used as the synthetic oil as the component (A), the mixing stability between the poly- α -olefin and the fluidity improver as the component (B) is improved.

On the other hand, the fluidity improver acts to improve the fluidity of a hydrocarbon compound at low temperatures (those of evaporator) in the presence of a small amount of a substitute flon refrigerant such as R-134a, so as to provide better returnability of the lubricant in a refrigerating cycle. The kinematic viscosity of the fluidity improver is not particularly limited but ordinarily is 2 to 100cSt, preferably 3 to 50cSt at 40°C.

Typical examples of the fluidity improver include an ester compound, particularly an ester compound having at least 2 ester bonds. A variety of these ester compounds can be used and an appropriate ester compound may be selected from them according to the intended use. Preferred among them is a reaction product as set forth in any of (I) to (V) below:

(I) A reaction product of ① a polybasic carboxylic acid or its derivative, ② a polyhydric alcohol or its derivative and ③ a monobasic fatty acid or its derivative.

45 (II) A reaction product of ① a polybasic carboxylic acid or its derivative, ② a polyhydric alcohol or its derivative and ④ a monohydric aliphatic alcohol or its derivative.

(III) A reaction product of ② a polyhydric alcohol or its derivative and ③ a monobasic fatty acid or its derivative (preferably an equivalent reaction product).

(IV) A reaction product of ④ a monohydric aliphatic alcohol or its derivative and ① a polybasic carboxylic acid or its derivative.

50 (V) A reaction product of ① a polybasic carboxylic acid or its derivative and ② a polyhydric alcohol or its derivative.

Various polybasic carboxylic acids ① can be used herein, and their preferred examples include an aliphatic saturated dicarboxylic acid having 2 to 12 carbon atoms (oxalic acid, malonic acid, succinic acid, glutaric acid, adipic acid, pimelic acid, suberic acid, azelaic acid, sebacic acid, dodecanoic-2 acid and the like), an aliphatic unsaturated dicarboxylic acid having 4 to 14 carbon atoms (maleic acid, fumaric acid, alkenylsuccinic acid and the like) and an aromatic dicarboxylic acid having 8 carbon atoms (phthalic acid, isophthalic acid, terephthalic acid and the like), a dicarboxylic acid such as epoxide of epoxyhexahydrophthalic acid and a tribasic or higher carboxylic acid such as citric acid, trimellitic acid and pyromellitic acid.

Examples of their derivative include monoester, diester, metal salt, anhydride, acid chloride and the like of these polybasic carboxylic acids.

Examples of the polyhydric alcohol ② include glycols (ethylene glycol; diethylene glycol; triethylene glycol; tetraethylene glycol; polyethylene glycol; propylene glycol; dipropylene glycol; polypropylene glycol; 1,2-butylene glycol; 1,3-butylene glycol; 1,4-butylene glycol; 2,3-butylene glycol; polybutylene glycol; 2-methyl-2,4-pentanediol; 2-ethyl-1,3-hexanediol and the like), glycerin, hindered alcohol (neopentyl glycol, trimethylolpropane, pentaerythritol, dipentaerythritol and the like), sorbitol and sorbitan. Examples of their derivative include acid chloride, metal salt and the like.

Furthermore, various monobasic fatty acids ③ (including primary, secondary and tertiary compounds) can be used herein, and a monobasic fatty acid containing an alkyl group having 1 to 20 carbon atoms, particularly a branched alkyl group having 3 to 18 carbon atoms, and more particularly a branched alkyl group having 4 to 12 carbon atoms is preferable because of their marked effect on improving the fluidity of the lubricant. Their specific examples include acetic acid; propionic acid; iso-propionic acid; butyric acid; iso-butyric acid; pivalic acid; n-valeric acid; iso-valeric acid; caproic acid; 2-ethylbutyric acid; n-caproic acid; 2-methylcaproic acid; n-heptylic acid; n-octanoic acid; 2-ethylhexanoic acid; 3,5,5-trimethylhexanoic acid; nonanoic acid; tert-nonanoic acid, dodecanoic acid; lauric acid and the like). Examples of their derivatives include ester, metal salt, acid chloride, anhydride and the like.

Various monohydric aliphatic alcohols or their derivatives ④ can be used herein, and a monohydric aliphatic alcohol or its derivative containing an alkyl group having 1 to 20 carbon atoms, particularly a branched alkyl group having 3 to 18 carbon atoms and more particularly a branched alkyl group having 4 to 12 carbon atoms is preferable because of their marked effect on improving the fluidity of the lubricant. Their specific examples include methyl alcohol, ethyl alcohol, n-propyl alcohol, iso-propyl alcohol, n-butyl alcohol, iso-butyl alcohol, sec-butyl alcohol, tert-butyl alcohol, n-amyl alcohol, iso-amyl alcohol, tert-amyl alcohol, diethyl carbinol, n-hexyl alcohol, methylamyl alcohol, ethylbutyl alcohol, heptyl alcohol, methylamyl carbinol, dimethylpentyl alcohol, n-octyl alcohol, sec-octyl alcohol, 2-ethylhexyl alcohol, iso-octyl alcohol, n-nonyl alcohol, diisobutyl carbinol, n-decyl alcohol, iso-decyl alcohol and the like. Examples of their derivatives include chloride, metal salt and the like.

It is preferable that above-mentioned ester compound should have a predetermined kinematic viscosity and be a reaction product as set forth in any of (I) to (V) above. The reaction product (I) can be obtained by reacting the compounds as enumerated in ①, ② and ③ above. For the reaction product (I) every detail of its structure has not necessarily been brought to light. Ordinarily, however, the reaction product (I) has a structure wherein 2 carboxyl groups of the polybasic carboxylic acid ① (in the case with a derivative thereof, groups derived from the carboxyl groups; the same shall apply hereunder) each react to be bonded with a hydroxyl group of the polyhydric alcohol ② (in the case with a derivative thereof, groups derived from the hydroxyl groups; the same shall apply hereunder) and further another hydroxyl group of this polyhydric alcohol ② reacts to be bonded with a carboxyl group of the monobasic fatty acid ③. Meanwhile, the rest of carboxyl groups of the polybasic carboxylic acid ① and the rest of hydroxyl groups of the polyhydric alcohol ② may remain as the carboxyl group and hydroxyl group respectively, as they are or react with other functional groups.

The reaction product (II) can be obtained by reacting the compounds as enumerated in ①, ② and ④ above. For this reaction product (II) every detail of its structure has not necessarily been brought to light. Ordinarily, however, the reaction product (II) has a structure wherein 2 hydroxyl groups of the polyhydric alcohol ② each react to be bonded with a carboxyl group of the polybasic carboxylic acid ① and further the remaining carboxyl group of this polybasic carboxylic acid ① reacts to be bonded with a hydroxyl group of the monohydric aliphatic alcohol ④. Meanwhile, the rest of carboxyl groups of the polybasic carboxylic acid ① and the rest of hydroxyl groups of the polyhydric alcohol ② may remain as the carboxyl group and hydroxyl group respectively, as they are or react with other functional groups.

These synthetic oils (A) and fluidity improvers (B) are mixed at a ratio by weight of 40 to 95%, desirably 5 to 90%, particularly desirably 55 to 90%, most desirably 60 to 90% of (A) to 5 to 60%, desirably 10 to 50%, particularly desirably 10 to 45%, most desirably 10 to 40%, respectively of (B).

The fluidity of the lubricant is undesirably not improved when less than 5% by weight of the fluidity improver is used, resulting in insufficient returnability of the lubricant. When more than 60% by weight of the fluidity improver is used, wear resistance is undesirably lowered, accompanied by the degradation of the fundamental performance required of refrigerating machine lubricant including decrease in insulation resistance, worsening of hydrolytic stability, increase in hygroscopicity and the like.

As set forth above, the lubricant of the present invention comprises the synthetic oil (A) and the fluidity improver (B) as the essential component, but various additives can be incorporated therein as the need arises. Examples of the additive include an anti-wear additive such as phosphoric acid ester and

phosphorous acid ester, an antioxidant, a chlorine scavenger, a metal deactivator, a defoaming agent, a detergent-dispersant, a viscosity index improver, a rust preventive, a corrosion inhibitor and the like.

As set forth above, the lubricant for refrigerating machines employing a refrigerant comprising tetrafluoroethane, as claimed herein, is excellent in the performance such as wear resistance, electrical insulating properties, hydrolytic stability, nonhygroscopicity and the like and especially has excellent returnability of the lubricant. The lubricant can be used along with a substitute flon refrigerant in a compression-type refrigerating cycle without a hitch.

Thus, the lubricant of the present invention is especially effective when used in automobile or household air conditioner, refrigerator and the like, having high industrial usefulness.

The present invention will now be described in greater detail below with reference to non-limitative examples and comparative examples.

Examples 1 to 8 and Comparative Examples 1 to 3

The synthetic oils and the fluidity improvers were mixed as shown in Table 1 to prepare the lubricants for use in the following tests. The results thereof are given in Table 2.

Table 1

	Mixing Composition			
	Synthetic Oil		Fluidity Improver	
	Compound	Wt%	Compound	Wt%
Example 1	Poly- α -olefinI ^{*1}	80	Ester A ^{*4}	20
Example 2	Poly- α -olefinI ^{*1}	60	Ester A ^{*4}	40
Example 3	Poly- α -olefinI ^{*1}	70	Ester B ^{*5}	30
Example 4	Poly- α -olefinI ^{*1}	70	Triglyceride ^{*6}	30
Example 5	Poly- α -olefinII ^{*2}	60	Ester A ^{*4}	40
Example 6	Poly- α -olefinI ^{*1} Alkylbenzene ^{*3}	50 30	Ester A ^{*4}	20
Example 7	Poly- α -olefinI ^{*1} Alkylbenzene ^{*3}	40 20	Ester A ^{*4}	40
Example 8	Poly- α -olefinI ^{*1} Alkylbenzene ^{*3}	50 30	Ester B ^{*5}	20
Comparative Example 1	Alkylbenzene ^{*3}	80	Ester B ^{*5}	20
Comparative Example 2	Poly- α -olefinI ^{*1}	30	Ester A ^{*4}	70
Comparative Example 3	Poly- α -olefinI ^{*1} Alkylbenzene ^{*3}	10 10	Ester B ^{*5}	80

Table 2

		Performance	
		Fluidity at low temperatures (relative value)	Wear resistance
5			
10	Example 1	20	○
	Example 2	20	○
15	Example 3	18	○
	Example 4	16	○
	Example 5	22	○
20	Example 6	30	○
	Example 7	25	○
25	Example 8	40	○
	Comparative Example 1	100	○
30	Comparative Example 2	20	×
	Comparative Example 3	20	×
35			

40

45

50

55

Table 2 (continued)

	Performance		
	Insulation resistivity ($\Omega \cdot \text{cm}$)	Hydrolysis	Hygroscopicity
Example 1	6.8×10^{14}	○	○
Example 2	8.2×10^{13}	△	○
Example 3	2.2×10^{14}	○	○
Example 4	8.8×10^{13}	○	○
Example 5	8.0×10^{13}	△	○
Example 6	3.2×10^{14}	○	○
Example 7	7.2×10^{13}	○	○
Example 8	1.2×10^{13}	○	○
Comparative Example 1	3.0×10^{14}	○	○
Comparative Example 2	1.5×10^{13}	×	△
Comparative Example 3	1.2×10^{13}	×	△

All the lubricants used were mixed with 0.5% by weight of an anti-wear additive (phosphoric acid ester). The notes in the tables will be supplemented below:

- *1: A polymer of 1-decene (a kinematic viscosity of 32cSt at 40°C).
- *2: A polymer of 1-decene (a kinematic viscosity of 46cSt at 40°C).
- *3: Soft alkylbenzene (a kinematic viscosity of 38cSt at 40°C).
- *4: An ester of C₇ fatty acid and pentaerythritol (a kinematic viscosity of 30cSt at 40°C).
- *5: An ester of C₇ fatty acid and trimethylolpropane (a kinematic viscosity of 14cSt at 40°C).
- *6: 2-ethylhexyltriglyceride (a kinematic viscosity of 16cSt at 40°C).

The lubricants were evaluated by determining each aspect of their performance thereof in accordance with the following test method:

EP 0 556 662 A1

Evaluation of the performance

(1) Fluidity of the lubricants at low temperatures

5 A lubricant mixed with 10% of R-134a was collected into a pressure glass tube having a diameter of 8mm, a steel ball of 3/16in in diameter was introduced therein and the pressure glass tube was sealed.

After the pressure glass tube was retained at -45 °C, the steel ball was caused to fall to determine the time (second) required until the steel ball reached a point 10cm to 5cm above the bottom of the tube. The result thereof is given in terms of a relative value.

10

(2) Wear resistance

The wear resistance was tested under the following conditions by using a Falex friction testing machine.

15 R-134a was blown at a rate of 5 liter/hr, and a test piece was subjected to wear for 60 minutes under a load of 300lbs and at 1,000rpm. The test pieces such as block and pin were made of a standard material in accordance with ASTM D-3233.

Standard of evaluation (amount of wear)

- 20 O: Less than 6.0mg
Δ: 6.0mg or more to 15mg or less
X: More than 15mg

(3) Electrical insulating properties

25

The electrical insulating properties was evaluated mutatis mutandis according to JIS C-2101 to determine the volume resistivity (room temperature).

(4) Hydrolytic stability

30

100g of a lubricant, 10g of R-134a, 5ml of water and iron and copper catalysts were placed in a pressure container having a capacity of 300cc. Then, the container was sealed and retained at 100 °C for 5 days and thereafter the rate of a rise of the total acid number was determined.

35 Standard of evaluation

- O: Less than 0.01mgKOH/g
Δ: 0.01mgKOH/g or more to 0.1mgKOH/g or less
X: More than 0.1mgKOH/g

40

(5) Hygroscopicity

10g of a test sample was placed in a 50cc glass container having a diameter of 30mm. The glass container was introduced into a thermostat-humidistat and allowed to stand for 5 days at a temperature of 25 °C and under a humidity of 85%, and then the water content of the test sample was determined.

45

Standard of evaluation

- 50 O: less than 0.3%
Δ: 0.03% or more to 0.1% or less
X: More than 0.1%

Claims

- 55 1. A lubricant for refrigerating machines employing a refrigerant comprising 1,1,1,2-tetrafluoroethane or 1,1,2,2-tetrafluoroethane which comprises as an essential component a base oil comprising (A) 40 to 95% by weight of a synthetic oil formed of a poly- α -olefin or a mixture of a poly- α -olefin and an alkylbenzene and (B) 5 to 60% by weight of a fluidity improver formed of at least one member selected

from an ester compound and a triglyceride.

2. The lubricant according to Claim 1, wherein said poly- α -olefin is a polymer of an α -olefin having 8 to 14 carbon atoms and a kinematic viscosity of 10 to 350cSt at 40 °C.
3. The lubricant according to Claim 2, wherein said polymer of an α -olefin is a polymer of 1-dodecene, 1-decene or 1-octene, each having a kinematic viscosity of 10 to 350cSt at 40 °C.
4. The lubricant according to Claim 1, wherein said alkylbenzene is selected from a soft alkylbenzene or a hard alkylbenzene, each having a kinematic viscosity of 10 to 350cSt at 40 °C.
5. The lubricant according to Claim 1, wherein said mixture of the poly- α -olefin and the alkylbenzene has a poly- α -olefin content of 50% or more by weight of the mixture.
6. The lubricant according to Claim 1, wherein said fluidity improver (B) has a kinematic viscosity of 3 to 50cSt at 40 °C.
7. The lubricant according to Claim 1, wherein said ester compound has 2 or more ester bonds.
8. The lubricant according to Claim 7, wherein said ester compound is selected from:
 - (I) a reaction product of ① a polybasic carboxylic acid or a derivative thereof, ② a polyhydric alcohol or a derivative thereof and ③ a monobasic fatty acid or a derivative thereof,
 - (II) a reaction product of ① a polybasic carboxylic acid or a derivative thereof, ② a polyhydric alcohol or a derivative thereof and ④ a monohydric aliphatic alcohol or a derivative thereof,
 - (III) an equivalent reaction product of ② a polyhydric alcohol or a derivative thereof and ③ a monobasic fatty acid or a derivative thereof,
 - (IV) a reaction product of ④ a monohydric aliphatic alcohol or a derivative thereof and ① a polybasic carboxylic acid or a derivative thereof, or
 - (V) a reaction product of ① a polybasic carboxylic acid or a derivative thereof and ② a polyhydric alcohol or a derivative thereof.
9. The lubricant according to Claim 1, which comprises 60 to 90% by weight of the synthetic oil (A) and 10 to 40% by weight of the fluidity improver (B).
10. A method for effecting lubrication in refrigerating machines employing a refrigerant comprising 1,1,1,2-tetrafluoroethane or 1,1,2,2-tetrafluoroethane which comprises as an essential component a base oil comprising (A) 40 to 95% by weight of a synthetic oil formed of a poly- α -olefin or a mixture of a poly- α -olefin and an alkylbenzene and (B) 5 to 60% by weight of a fluidity improver formed of at least one member selected from an ester compound and a triglyceride.
11. A refrigerating system which comprises a compressor, a refrigerant comprising 1,1,1,2-tetrafluoroethane or 1,1,2,2-tetrafluoroethane, and a lubricant, said lubricant comprising a base oil according to any one of Claims 1 to 9.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 93 10 1779
Page 1

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
X	US-A-4 175 047 (J.W. SCHICK) * claims 1-4 * * column 3, line 33 - line 41 * * column 4; table 1 * * column 4; table 2 * ---	1-3,6-9	C10M111/04 C10M169/04 C10M171/00 //(C10M111/04, 105:06,105:36, 105:38,105:42, 107:10) (C10M169/04, 105:06,107:10, 129:72,129:74, 129:78) (C10N40:30)
X	EP-A-0 440 069 (KAO CORPORATION) * page 4, line 58 - page 5, line 12 * * claim 1 * * page 6; example 1; table 1 * ---	1,6-8, 10,11	
X	EP-A-0 415 778 (KAO CORPORATION) * page 5, line 15 - line 25 * * page 7; example 1; table 1 * * claims 1,3 * ---	1,6-8, 10,11	
X	EP-A-0 413 315 (QUATUM CHEMICAL CORPORATION) * page 15, line 1 - line 12 * * claim 16 * ---	1-3,6-9	
A	EP-A-0 470 788 (NIPPON OIL COMPANY) * page 5, line 9 - line 24 * ---	1-3,6-8, 10,11	C10M C09K
A	US-A-3 733 850 (S.A. OLUND) * claim 1 * ---	4,5	
A	FR-A-2 299 398 (MOBIL OIL CORPORATION) * page 5, line 37 - page 6, line 11 * ---		
-/--			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 MAY 1993	Examiner HILGENGA K.J.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document			

EPO FORM 1503 (12.92) (P0401)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 93 10 1779

Page 2

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
A	DATABASE WPIL Week 8805, Derwent Publications Ltd., London, GB; AN 88-033105 & JP-A-62 292 895 (NIPPON OILS & FATS) 19 December 1987 * abstract * -----		
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 MAY 1993	Examiner HILGENGA K.J.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document			

EPO FORM 1503 01.82 (P0601)